



ECO12LDT
ECO20LDT

- ✓ Convenient Carry Handle
- ✓ Tank Full Auto Shut
- ✓ Auto Restart After Power Cut
- ✓ Continuous Drain Option
- ✓ Water Level Indicator Window
- ✓ Simple To Use Rotary Switch Control
- ✓ Washable Mesh Filter

Model			ECO12LDT	ECO20LDT
Convenient Carry Handle			✓	✓
Tank Full Auto Shut			✓	✓
Auto Restart After Power Cut			✓	✓
Continuous Drain Option			✓	✓
Water Level Indicator Window			✓	✓
Simple To Use Rotary Switch Control			✓	✓
Washable Mesh Filter			✓	✓
Power supply		Ph-V-Hz	1-220~240V-50HZ	1-220~240V-50HZ
Moisture removal	30°C,RH80%	L/Day	12	20
Power consumption	30°C,RH80%	W	220	555
Operating current	30°C,RH80%	A	1.3	3
Air flow volume		m3/h	130	168
Applicable area		m2	10 - 17	18 - 30
Noise level		dB(A)	45	50
Water tank volume		L	1.5	3.2
Net Dimension (W*H*D)		mm	330 * 420 * 260	380 * 480 * 300
Net/Gross weight		Kg	9.5 / 13	13.5 / 15
Ambient temp		°C	5 - 35	5 - 35